



- Salt & water savings
- 6 lbs of salt per cubic foot of resin
- Superior clearwater iron removal
- Less susceptible to fouling by iron
- More tolerant of chlorine
- Performs better than standard resin in water with elevated TDS
- Uses less water per regeneration than a standard water softener!
- Ready out of box to connect to 1" or 3/4" plumbing

SWS1-HE Series

High Efficiency Water Softener



A water softener you can feel good about!

Regenerates with only 6 lbs salt per cubic foot. This represents a 33% less salt per regeneration when compared to standard water softeners. Not only do you save substantial dollars, but you reduce the hassle of carrying salt.

SWS1-HE water softeners utilize a revolutionary new resin that has higher cross linkage resulting in less salt usage, greater softening capacity, better iron removal, and is more tolerant of chlorine.

| Model Number | Grain Capacity | | Type of Regeneration | Flow Rate (gpm) | | Resin Volume | Overall Dimensions | | | Salt Storage | Pipe Size |
|--------------|----------------|--------|----------------------|-----------------|---------|--------------|--------------------|-----|-----|--------------|-----------|
| | Max. | Std. | | Peak | Service | | D | W | H | | |
| SWS1-30-HE | 31,000 | 22,000 | Meter | 18 | 8 | 1.0 | 18" | 27" | 56" | 220 lbs | 3/4" & 1" |
| SWS1-45-HE | 46,500 | 33,000 | | 18 | 12 | 1.5 | 18" | 28" | 62" | | |
| SWS1-60-HE | 62,000 | 44,000 | | 23 | 14 | 2.0 | 18" | 30" | 56" | | |
| SWS1-75-HE | 77,500 | 55,000 | | 22 | 18 | 2.5 | 18" | 31" | 62" | | |
| SWS1-90-HE | 93,000 | 66,000 | | 26 | 19 | 3.0 | 23" | 37" | 76" | 600 lbs | |
| SWS1C-30-HE | 31,000 | 22,000 | Meter (space saver) | 21 | 8 | 1.0 | 16" | 23" | 43" | 120 lbs | |

NOTE: Service flow rate of control valve with bypass and meter is 27gpm @ 15 psig drop.



www.sterlingwatertreatment.com

